



Main

Device application	Distribution
Range	Domae
Product or component type	Miniature circuit-breaker
Poles description	1P
Number of protected poles	1
[In] rated current	4 A
Network type	AC
Curve code	C
Breaking capacity	4500 A conforming to IEC 60898-1 - 230 V AC 50 Hz

Complementary

Network frequency	50 Hz
[Ue] rated operational voltage	220...240 V AC 50 Hz
Control type	Toggle
Mounting mode	Clip-on
Mounting support	DIN rail
Comb busbar and distribution block compatibility	YES
9 mm pitches	2
Colour	Grey

Environment

Standards	IEC 60898-1 SNI 04-6507.1
Product certifications	SNI

Disclaimer: Dokumentasi ini tidak ditujukan sebagai pengganti dan tidak digunakan untuk menentukan kesesuaian atau keandalan produk ini untuk aplikasi pengguna

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0627 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months 12 months
-----------------	---------------------