



Main

| | |
|---------------------------|---|
| Device application | Distribution |
| Range | Domae |
| Product or component type | Miniature circuit-breaker |
| Poles description | 2P |
| Number of protected poles | 2 |
| [In] rated current | 25 A |
| Network type | AC |
| Curve code | C |
| Breaking capacity | 4500 A conforming to IEC 60898-1 - 230 V AC 50 Hz |

Complementary

| | |
|--|----------------------|
| Network frequency | 50 Hz |
| [Ue] rated operational voltage | 220...240 V AC 50 Hz |
| Control type | Toggle |
| Mounting mode | Clip-on |
| Mounting support | DIN rail |
| Comb busbar and distribution block compatibility | YES |
| 9 mm pitches | 4 |
| Colour | Grey |

Environment

| | |
|------------------------|------------------------------|
| Standards | IEC 60898-1 SNI 04-6507.1 |
| Product certifications | SNI |

Offer Sustainability

| | |
|----------------------------------|---|
| Sustainable offer status | Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 0627 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold |
| Product environmental profile | Available |
| Product end of life instructions | Need no specific recycling operations |

Contractual warranty

| | |
|-----------------|---------------------|
| Warranty period | 18 months 12 months |
|-----------------|---------------------|