



Main

Range	Acti 9
Product name	Acti 9 STI
Product or component type	Fuse-disconnector
Device short name	STI
Poles description	3P + N

Complementary

[In] rated current	10 A 16 A 2 A 20 A 25 A 4 A 6 A
Fuse curve	AM GG
Fuse size	10.3 x 38 mm
[Ue] rated operational voltage	500 V AC
[Ui] rated insulation voltage	500 V AC 50/60 Hz
Mounting mode	Clip-on
Mounting support	DIN rail
9 mm pitches	6
Height	81 mm
Width	54 mm
Depth	75 mm
Colour	White
Connections - terminals	Screw clamp terminals 1 cable(s) 0.75...10 mm ² rigid Screw clamp terminals 2 cable(s) 0.75...4 mm ² rigid Screw clamp terminals 1 cable(s) 0.5...6 mm ² flexible

Screw clamp terminals 2 cable(s) 0.5...6 mm² flexible

Wire stripping length	12 mm
Tightening torque	2 N.m

Environment

Standards	IEC 60269-1/2 IEC EN 60947-3
IP degree of protection	IP20
Pollution degree	3
Ambient air temperature for operation	-20...60 °C
Ambient air temperature for storage	-40...80 °C

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1105 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	12 months
-----------------	-----------