



### Main

Product or component type	Cartridge
Device short name	C neutral-350
Surge arrester type	Electrical distribution network

### Complementary

Surge arrester class type	Type 2
Surge arrester technology	GDT
Earthing system	TN TT
[Ue] rated operational voltage	230 V AC 50 Hz
Nominal discharge current	20 kA
Maximum discharge current	65 kA
[Uc] maximum continuous operating voltage	260 V
[Up] voltage protection level	1.4 kV type 2
Local signalling	Flag color: white/red
Mounting mode	Plug-in
Mounting support	Into SPD module
9 mm pitches	2
Height	57 mm
Width	18 mm
Depth	56 mm
Product weight	0.044 kg
Colour	White ( RAL 9003 )
Material	PBT (polybutylene terephthalate)
Response time	< 100 ns

Disklaimer: Dokumentasi ini tidak ditujukan sebagai pengganti dan tidak digunakan untuk menentukan kesesuaian atau keandalan produk ini untuk aplikasi pengguna

## Environment

Standards	EN 61643-11 IEC 61643-11: 2011
Product certifications	CE
IP degree of protection	Front face : IP20
Relative humidity	5...90 %
Operating altitude	0...2000 m
Ambient air temperature for operation	-25...60 °C
Ambient air temperature for storage	-40...85 °C

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0844 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available <a href="#">Product environmental</a>
Product end of life instructions	Available <a href="#">End of life manual</a>

## Contractual warranty

Warranty period	18 months 12 months
-----------------	---------------------