



### Main

Range	TeSys
Product or component type	Contactor coil
Device short name	LX1FF
Range compatibility	TeSys F LC1F contactor
Product compatibility	LC1F115 LC1F150
Control circuit type	AC 50/60 Hz
[Uc] control circuit voltage	265...277 V AC 60 Hz 220...230 V AC 50 Hz
Average resistance	28.1 Ohm at 20 °C
Inductance of closed circuit	3.44 H
Operating time	23...35 ms closing 5...15 ms opening
Mechanical durability	10 Mcycles
Operating rate	<= 2400 cyc/h at <= 55 °C

### Complementary

Coil technology	Without built-in suppressor module
Control circuit voltage limits	0.35...0.55 Uc at 55 °C drop-out 50/60 Hz 0.85...1.1 Uc at 55 °C operational 50/60 Hz
Inrush power in VA	550 VA at 20 °C (cos f 0.3) 50 Hz 660 VA at 20 °C (cos f 0.3) 60 Hz
Hold-in power consumption in VA	45 VA at 20 °C (cos f 0.3) 50 Hz 55 VA at 20 °C (cos f 0.3) 60 Hz
Heat dissipation	12...16 W at 50/60 Hz

### Environment

Ambient air temperature for operation	> -5...55 °C
Product weight	0.43 kg

### Contractual warranty

Warranty period	18 months
-----------------	-----------