



DL LED CS-AK-osp-023 (WW) / 024 (CDL)

DL LED CS-AK-osp-025 (WW) / 026 (CDL)

DL LED CS-AK-osp-027 (WW) / 028 (CDL)

DL LED CS-AK-osp-029 (WW) / 030 (CDL)

Material	aluminum	aluminum	aluminum	aluminum
Finish color	ivory white	ivory white	ivory white	ivory white
Cut-out size	120 mm	120 mm	155 mm	155 mm
Mounting range	flat	flat	flat	flat
Ip grade	Ip 20	Ip 20	Ip 20	Ip 20
Working temperature	-10—45°C	-10—45°C	-10—45°C	-10—45°C
Net weight	400 G	425 G	450 G	519 G
Qty/ctn	12 pcs/ctn	12 pcs/ctn	8 pcs/ctn	8 pcs/ctn
Luminous efficiency	70 Lm/w	70 Lm/w	65 Lm/w	65 Lm/w
LED chip	Bridgelux (from USA)	Bridgelux (from USA)	38 pcs / SMD30	38 pcs / SMD30
Lumen	1050 Lm / 975 Lm	1050 Lm / 975 Lm	675 Lm / 900 Lm	675 Lm / 900 Lm
CRI	Ra >80	Ra >80	Ra >80	Ra >80
Power	15 W	15 W	15 W	15 W
Color temperature	3000 K [CS-AK-OSP-023 WW] 6000 K [CS-AK-OSP-024 CDL]	3000 K [CS-AK-OSP-025 WW] 6000 K [CS-AK-OSP-026 CDL]	3000 K [CS-AK-OSP-027 WW] 6000 K [CS-AK-OSP-028 CDL]	3000 K [CS-AK-OSP-029 WW] 6000 K [CS-AK-OSP-030 CDL]
Lifespan	25,000 hrs	25,000 hrs	25,000 hrs	25,000 hrs
Voltage	170—240 VAC	170—240 VAC	170—240 VAC	170—240 VAC
Beam angle	30°	30°	90°	90°
Application	Shop, supermarket, store, hall, showroom, office, hotel, restaurant and so on...			

Light size



Below coordinate the light intensity distribution curve

