

LED FLOODLIGHT 50 W

Flood light with integrated LED light can be used on indoor as well as outdoor. Good to replace high intensity discharge lamps up to 250 W. Used for your courtyard, park and building wall.



FEATURES

LED working voltage: 30 to 36 V DC
 LED quantity: 1 piece
 LED power: 50 W
 LED Luminous efficiency: 80 lm/W
 IP rate: IP 65

APPLICATION

This industrial light can be used in variety of indoor and outdoor places, such as in factory stadium, wart, advertisement board, park and tunnel.

TECHNICAL SPECIFICATION

Parts No	C3-AK-07P-007 (CCL) C3-AK-07P-008 (WW)	
Range Input Voltage	AC 85 - 285 V	
Rated Input Voltage	AC 110 - 220 V	
Frequency	50 - 60 Hz	
Average LifeTime	Up to 50,000 hrs	
Operating Temperature	-20 ~ 55 °C	
Color Temperature	Cool Day Light	6000 - 6500 K
	Warm White	2700 - 3000 K
Luminous Flux	Cool Day Light	3500 lm ± 10%
	Warm White	3500 lm ± 10%
IP Rate	IP65	
Color Rendering Index	≥ 80	



angle 131.71°

0.5 m	2.2 m
1.0 m	4.4 m
1.5 m	6.6 m
2.0 m	8.8 m
2.5 m	11.0 m
3.0 m	13.2 m