



ESSENTIAL

ESSENTIAL 50W CDL E27 220-240V 1CC/6

The Essential range is a standard stick-shape compact fluorescent lamp, with the lowest purchase price. It is available in 8W, 14W, 18W and 23W, with lumen equivalence of 40W, 75W, 100W and 125W incandescent light bulb. It is also available in two color temperatures: warm white (2700K) and cool daylight (6500K). It is available in both 220-240V and 120-127V and able to operate under a wide voltage range (Power supply fluctuation). It consumes up to 80% less energy than the incandescent light bulb and lasts for 3 years.

Product data

General Information	
Cap-Base	E27 [E27]
Light Technical	
Color Code	865 [CCT of 6500K]
Luminous Flux (Nom)	3100 lm
Color Designation	Cool Daylight
Lumen Maintenance 2000 h (Nom)	85 %
Lumen Maintenance 5000 h (Nom)	75 %
Chromaticity Coordinate X (Nom)	313
Chromaticity Coordinate Y (Nom)	337
Correlated Color Temperature (Nom)	6500 K
Luminous Efficacy (Rated) (Nom)	62 lm/W
Color Rendering Index (Min)	80
LLMF at End of Nominal Lifetime (Min)	65 %
Operating and Electrical	
Input Frequency	50 or 60 Hz


Power (Rated) (Nom)	50 W
Lamp Current (Nom)	240 mA
Power Factor (Nom)	0.6
Voltage (Nom)	220-240 V
Product Data	
Full product code	692341076892300
Order product name	ESSENTIAL 50W CDL E27 220-240V 1CC/6
EAN/UPC - Product	6923410768923
Order code	929689844699
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	6
Material Nr. (12NC)	929689844699
Net Weight (Piece)	0.380 kg

ESSENTIAL

Warnings and Safety

- Breaking a lamp is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a closed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.
- Compact fluorescent lamps have to be treated as special waste, they must be taken to your local waste facilities for recycling. The European Lighting Industry has set up an infrastructure, capable of recycling mercury, other metals, glass etc.

Dimensional drawing



Product	D (max)	C (max)	F (max)
ESSENTIAL 50W CDL E27 220-240V 1CC/6	67.9 mm	292.5 mm	87 mm

Economy 50W/865 E27 220-240V 50/60Hz

