



Main

Range	Mini Pragma
Product or component type	Enclosure
Enclosure type	Modular enclosure
Nb of 18 mm modules per row	18
Nb of horizontal rows	1
Type of door	Plain
Width	378 mm wall 402 mm outside
Height	228 mm wall 252 mm outside
Depth	98 mm total 18 mm outside 80 mm wall
Built-in depth	80 mm

Complementary

Enclosure mounting	Flush
9 mm pitches	36
Total number of 18 mm modules	18
[In] rated current	63 A
Type of rail	35 mm asymmetrical rail
Cable entry	Pre-cutted holes
Terminal block function	Earth / neutral
Number of terminal blocks	1 earth terminal block with 16 screwed outgoers 1 neutral terminal block with 16 screwed outgoers
Distribution block outgoers	2 x 16 mm ² for earth 2 x 16 mm ² for neutral 6 x 6 mm ² for earth 6 x 6 mm ² for neutral

	8 x 10 mm ² for earth 8 x 10 mm ² for neutral
Enclosure material	Back part : technoplastic Door : technoplastic Front face : technoplastic
Colour	Door : white (RAL 9003) Front face : white (RAL 9003)

Environment

Standards	EN 50102 IEC 529 IEC 60439-3 IEC 60670-24 IEC 60695-2-11
Quality labels	IMQ
Fire resistance	Door : 650 °C Front face : 650 °C Back part : 650 °C
IP degree of protection	IP40
IK degree of protection	IK07
Ambient air temperature for operation	-25...60 °C

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0901 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available Product environmental
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months 12 months
-----------------	---------------------