Product data sheet
Characteristics

E8231BPL1_LS
10A 250V 1 Gang Bell Press Switch with Fluorescent Locator, Lavendar Silver

Main

Range of product	Pieno
Product or component type	Switch
Switch function	Momentary
Switch application	Bell
Rated current	10 A 250 V AC 50 Hz
Local signalling	Fluorescent white
Number of gangs	1 gang
Load type	Resistive
Cover frame colour tint	Lavender silver

Complementary

Wiring device mounting	Flush Surface
Material	Polycarbonate surround Polycarbonate grid plate
Connections - terminals	Pillar terminals
Number of cables	2 1.5 mm² stranded 2 2.5 mm² solid
Embedding depth	23 mm
Width	87 mm
Height	87 mm
Depth	23 mm

Environment

Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Standards	BS EN 60669-1 GB 16915.1 IEC 60669-1 MS IEC 60669-1 SS 227-1

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.