



Main

| | |
|---------------------------|-------------|
| Product or component type | USB charger |
| Fixing mode | Screw |

Complementary

| | |
|-------------------------------------|--|
| Device mounting | Flush |
| Device presentation | Mechanism |
| Colour tint | White |
| Surface finish | Glossy |
| Surface treatment | Untreated |
| Number of modules | 2 modules, with 46 x 36.7 x 21.7 mm |
| Condition of use | Room temperature |
| Ambient air temperature for storage | -5...60 °C |
| Relative humidity | 10...90 % |
| [Ue] rated operational voltage | 100/240 V, AC, 50/60 Hz |
| Integrated connection type | , 2 USB port, 5 V, DC, maximum load current: 2.1 A |
| Material | PA (polyamide) 6 for housing Silicone rubber for cover PC (polycarbonate) for grid plate |
| Shape of screw head | Cross |
| Number of terminals | 2-screw terminals |
| Clamping connection capacity | 2.5 mm ² (stranded) 2.5 mm ² (flexible) 2.5 mm ² (rigid) 1.5 mm ² (stranded) 1.5 mm ² (flexible) 1.5 mm ² (rigid) |
| Wire stripping length | 6 mm |
| Product compatibility | Apple Samsung HW XiaoMi HTC Major smart phone and tablet Power bank |
| Standards | IEC 60950-1 GB 4943.1 |

MS IEC 60950-1
CNS 14336
CNS 13438

| | |
|-----------------|-----------|
| Height | 87 mm |
| Width | 87 mm |
| Depth | 39 mm |
| Embedding depth | 29.3 mm |
| Product weight | 0.1107 kg |

Environment

| | |
|---------------------------------|------------------------|
| Product certifications | CCC IEC |
| IP degree of protection | IP20 |
| Environmental characteristic | Alcohol Liquid soap |
| Environmental health and issues | Halogen free |