

PL-C 4PIN

APPLICATIONS

Recessed or surface-mounted downlighter, wall units, pendant lamps and table lamps

FEATURES

Double glass forming technology reduces the glass tube breakages // Radio Interference suppression capacitor is installed
// Can be used in almost any light fittings



TYPE	POWER	LUMINOUS FLUX	COLOR TEMP.	CRI (Ra)	CURRENT	VOLTAGE	LENGTH	LIFE	CAP
PLC-2PI 10W G24q-1/827	10 W	600 lm	2700 K	82	0.19 A	64 V	114 mm	≥ 12000 h	G24q-1
PLC-2PI 10W G24q-1/840	10 W	600 lm	4000 K	82	0.19 A	64 V	114 mm	≥ 12000 h	G24q-1
PLC-2PI 10W G24q-1/865	10 W	580 lm	6500 K	82	0.19 A	64 V	114 mm	≥ 12000 h	G24q-1
PLC-2PI 13W G24q-1/827	13 W	900 lm	2700 K	82	0.175 A	91 V	137 mm	≥ 12000 h	G24q-1
PLC-2PI 13W G24q-1/840	13 W	900 lm	4000 K	82	0.175 A	91 V	137 mm	≥ 12000 h	G24q-1
PLC-2PI 13W G24q-1/865	13 W	870 lm	6500 K	82	0.175 A	91 V	137 mm	≥ 12000 h	G24q-1
PLC-2PI 18W G24q-3/827	18 W	1200 lm	2700 K	82	0.22 A	100 V	147 mm	≥ 12000 h	G24q-3
PLC-2PI 18W G24q-3/840	18 W	1200 lm	4000 K	82	0.22 A	100 V	147 mm	≥ 12000 h	G24q-3
PLC-2PI 18W G24q-3/865	18 W	1160 lm	6500 K	82	0.22 A	100 V	147 mm	≥ 12000 h	G24q-3
PLC-2PI 26W G24q-3/827	26 W	1800 lm	2700 K	82	0.325 A	105 V	168 mm	≥ 12000 h	G24q-3
PLC-2PI 26W G24q-3/840	26 W	1800 lm	4000 K	82	0.325 A	105 V	168 mm	≥ 12000 h	G24q-3
PLC-2PI 26W G24q-3/865	26 W	1750 lm	6500 K	82	0.325 A	105 V	168 mm	≥ 12000 h	G24q-3