

# PLC 2 PIN

## APPLICATIONS

Recessed or surface-mounted downlighter, wall units, pendant lamps and table lamps

## FEATURES

Double glass forming technology reduces the glass tube breakages // Radio interference suppression capacitor is installed

// Can be used in almost any light fittings



TYPE	POWER	LUMINOUS FLUX	COLOR TEMP.	CRI	CURRENT	VOLTAGE	LENGTH	LIFE	CAP
PLC- 211 10 W G24d-1/827	10 W	600 lm	2700 K	82	0.19 A	64 V	117 mm	≥ 12000 h	G24d-1
PLC- 211 10 W G24d-1/840	10 W	600 lm	4000 K	82	0.19 A	64 V	117 mm	≥ 12000 h	G24d-1
PLC- 211 10 W G24d-1/865	10 W	580 lm	6500 K	82	0.19 A	64 V	117 mm	≥ 12000 h	G24d-1
PLC- 211 13 W G24d-1/827	13 W	900 lm	2700 K	82	0.175 A	91 V	139 mm	≥ 12000 h	G24d-1
PLC- 211 13 W G24d-1/840	13 W	900 lm	4000 K	82	0.175 A	91 V	139 mm	≥ 12000 h	G24d-1
PLC- 211 13 W G24d-1/865	13 W	870 lm	6500 K	82	0.175 A	91 V	139 mm	≥ 12000 h	G24d-1
PLC- 211 18 W G24d-2/827	18 W	1200 lm	2700 K	82	0.22 A	100 V	151 mm	≥ 12000 h	G24d-2
PLC- 211 18 W G24d-2/840	18 W	1200 lm	4000 K	82	0.22 A	100 V	151 mm	≥ 12000 h	G24d-2
PLC- 211 18 W G24d-2/865	18 W	1160 lm	6500 K	82	0.22 A	100 V	151 mm	≥ 12000 h	G24d-2
PLC- 211 26 W G24d-3/827	26 W	1800 lm	2700 K	82	0.325 A	105 V	173 mm	≥ 12000 h	G24d-3
PLC- 211 26 W G24d-3/840	26 W	1800 lm	4000 K	82	0.325 A	105 V	173 mm	≥ 12000 h	G24d-3
PLC- 211 26 W G24d-3/865	26 W	1750 lm	6500 K	82	0.325 A	105 V	173 mm	≥ 12000 h	G24d-3