



PL-S 2 Pin

PL-S 11W/865/2P 1CT/25

PL-S is an efficient low-wattage compact fluorescent lamp, typically used for decorative and orientation purposes. The original Philips-invented bridge technology guarantees optimum performance in the application, enabling more light and higher efficacy than the bended technology. The 2-pin version is designed for operation on electromagnetic gear and is provided with a plug-in/pull-out lamp base.


Product data

General Information	
Cap-Base	G23 [G23]
Life to 50% Failures (Nom)	8000 h
Light Technical	
Color Code	865 [CCT of 6500K]
Luminous Flux (Nom)	900 lm
Color Designation	Cool Daylight
Lumen Maintenance 2000 h (Nom)	90 %
Lumen Maintenance 5000 h (Nom)	80 %
Correlated Color Temperature (Nom)	6500 K
Luminous Efficacy (Rated) (Nom)	72 lm/W
Color Rendering Index (Nom)	82
Operating and Electrical	
Power (Rated) (Nom)	11.6 W
Lamp Current (Nom)	0.160 A
Voltage (Nom)	89 V
Controls and Dimming	
Dimmable	No

Mechanical and Housing	
Cap-Base Information	2 Pins
Approval and Application	
Energy Efficiency Label (EEL)	A
Mercury (Hg) Content (Nom)	1.4 mg
Product Data	
Full product code	692341076141200
Order product name	PL-S 11W/865/2P 1CT/25
EAN/UPC - Product	6923410761412
Order code	927902386503
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	25
Material Nr. (12NC)	927902386503
Net Weight (Piece)	0.043 kg

PL-S 2 Pin

Dimensional drawing



Product	D (max)	D1 (max)	C (max)
PL-S 11W/865/2P 1CT/25	27.1 mm	13 mm	236.3 mm

PL-S 11W/865/2P

