Product datasheet Characteristics

DOM16790

earth leakage protection Domae - 2P - 25 A -220...240 V - 30 mA



Price*: 480150.00 IDR



Main

Range of product	Domae
Product or component type	Earth leakage protection
Poles description	2P
[In] rated current	25 A
Network type	AC
Earth-leakage sensitivity	30 mA
Earth-leakage protection time delay	Instantaneous

Complementary

Main	Domae	
	Domae	
Range of product		
Product or component type	Earth leakage protection	
Poles description	2P	
[In] rated current	25 A	
Network type	AC	
Earth-leakage sensitivity	30 mA	
Earth-leakage protection time delay	Instantaneous	
Complementary		
Network frequency	50 Hz	
[Ue] rated operational voltage	220240 V	
Control type	Toggle	
Mounting mode	Clip-on	
Mounting support	DIN rail	
Connection pitch	18 mm Between phases	
9 mm pitches	4	
Colour	Grey	
Environment		
Standards	IEC 60898-1 SNI 04-6507.1	
Product certifications	SNI	
Offer Sustainability		
Sustainable offer status	Green Premium product	
RoHS (date code: YYWW)	Compliant - since 0844 - Schneider Electric declaration of conformity	

Environment

		2
Standards	IEC 60898-1 SNI 04-6507.1	* *
Product certifications	SNI	

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0844 - Schneider Electric declaration of conformity

Schneider Electric declaration of conformity

REACh	Reference not containing SVHC above the threshold
	Reference not containing SVHC above the threshold
Product environmental profile	Available
	Product environmental
Product end of life instructions	Need no specific recycling operations