



Main

Range of product	Acti 9
Product or component type	Undervoltage release
Device short name	IMNs
[Uc] control circuit voltage	220...240 V AC 50/60 Hz
Control type	Delayed
9 mm pitches	2
Product compatibility	IC60 IID Single terminal Double terminal ISW-NA IDPN Vigi ARA RCA

Complementary

Range compatibility	Acti 9: Acti 9 iDPN (China version) Acti 9: Acti 9 iDPN Vigi Acti 9: Acti 9 iC40 Acti 9: Acti 9 iC65 Acti 9: Acti 9 ARA Acti 9: Acti 9 IID Acti 9: Acti 9 iSW-NA Acti 9: Acti 9 RCA Acti 9: Acti 9 iC60 (double terminals miniature circuit breaker)
Local signalling	Action indicator
Mounting mode	Clip-on
Mounting support	DIN rail
Width	18 mm
Colour	White
Connections - terminals	Clamp terminal 1 cable(s) 10 mm ² rigid

Clamp terminal 2 cable(s) 2.9 mm² rigid
Clamp terminal 1 cable(s) 8 mm² flexible
Clamp terminal 2 cable(s) 2.9 mm² flexible with cable end cable end

Tightening torque	1 N.m
-------------------	-------

Environment

Standards	EN/IEC 60947-5-1
Tropicalisation	2 conforming to EN/IEC 60947-5-1
Relative humidity	95 % at 55 °C
Ambient air temperature for operation	-25...50 °C
Ambient air temperature for storage	-40...85 °C

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1216 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available End of life manual
Product end of life instructions	Available

Contractual warranty

Warranty period	18 months 12 months
-----------------	---------------------