



### Main

Commercial Status	Commercialised
Range of product	Vivace
Device short name	KB15
Product or component type	Socket-outlet with switch
Device presentation	Complete mechanism

### Complementary

Outlet poles configuration	2P + E
Number of gangs	1 gang
Cover frame colour tint	White
Material	Polycarbonate (base) Polycarbonate (surround) Polycarbonate (grid plate)
Projecting depth	8 mm
Device mounting	Flush
Mounting support	Wall mounted
Fixing mode	By screw M3.5
Fixing center	60.3 mm
Embedding depth	>= 35 mm
Rated current	13 A at 250 V AC, resistive
Network frequency	50 Hz
Contacts material	Brass and phosphor bronze
Connections - terminals	Pillar terminal
Terminal identifier	N L Earth
Tightening torque	0.4 N.m
Clamping connection capacity	2 x 4 mm <sup>2</sup> 3 x 2.5 mm <sup>2</sup>
Width	87 mm
Height	87 mm

### Environment

Standards	MS 589 SS 145 BS 1362-2
Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Operating altitude	<= 2000 m
Environmental characteristic	Indoor use

### Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 0626 - <a href="#">Schneider Electric declaration of conformity</a>
------------------------	---

## Contractual warranty

---

Period	18 months
--------	-----------

---