



Main

Range	Vivace
Product or component type	Switch
Device short name	KB31
Device application	Bell switch
Device presentation	Complete mechanism
Additional switch application	Do not disturb

Complementary

Switch function	1-way
Actuator	Push-button
Pilot light	Indicator
Number of gangs	1 gang
Colour tint	White
Material	Polycarbonate (grid plate) Polycarbonate (surround) Nylon (base)
Projecting depth	8 mm
Device mounting	Flush
Mounting support	Wall mounted
Fixing mode	By screw M3.5
Fixing center	60.3 mm
Embedding depth	35 mm
Rated current	10 A at 250 V AC, inductive 10 A at 250 V AC, resistive
[Ue] rated operational voltage	250 V AC
Network frequency	50 Hz
Contacts material	Brass and phosphor bronze
Connections - terminals	Pillar terminal
Terminal identifier	COM L1 L2 N
Tightening torque	0.4 N.m

Disclaimer: Dokumentasi ini tidak ditujukan sebagai pengganti dan tidak untuk digunakan untuk menentukan kesesuaian atau keandalan produk ini untuk aplikasi pengguna

Clamping connection capacity	<= 1.5 mm ²
Width	86 mm
Height	86 mm

Environment

Standards	IEC 60669-1 MS IEC 60669-1 SS 227
Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Environmental characteristic	Indoor use