



Main

Commercial Status	Commercialised
Range of product	Vivace
Device short name	KB31
Product or component type	Switch
Device presentation	Complete mechanism
Switch application	Bell switch

Complementary

Switch function	1-way
Actuator	Rocker
Number of gangs	1 gang
Cover frame colour tint	White
Material	Polycarbonate (base) Polycarbonate (surround) Polycarbonate (grid plate)
Projecting depth	8 mm
Device mounting	Flush
Mounting support	Wall mounted
Fixing mode	By screw M3.5
Fixing center	60.3 mm
Embedding depth	>= 35 mm
Rated current	10 A at 250 V AC, inductive
[Ue] rated operational voltage	250 V AC
Network frequency	50 Hz
Contacts material	Brass and phosphor bronze
Connections - terminals	Pillar terminal
Terminal identifier	COM L1 L2
Tightening torque	0.4 N.m
Clamping connection capacity	1.5 mm ²
Width	87 mm
Height	87 mm

Environment

Standards	IEC 60669-1 MS IEC 60669-1 SS 227
Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Environmental characteristic	Indoor use

Offer Sustainability

RoHS (date code: YYWW)

Compliant - since 0626 - [Schneider Electric declaration of conformity](#)

Contractual warranty

Period	18 months
--------	-----------
