
# Product data sheet Characteristics

## KB31IA

## 16AX 250V Intermediate Switch



## Main

Device presentation	Complete mechanism
Product or component type	Switch
Device short name	KB31
Range of product	Vivace
Commercial Status	Commercialised

#### Complementary

Complementary	
Switch function	Intermediate
Actuator	Rocker
Number of gangs	1 gang
Cover frame colour tint	White
Material	Nylon (base) Polycarbonate (surround) Polycarbonate (grid plate)
Projecting depth	8 mm
Device mounting	Flush
Mounting support	Wall mounted
Fixing mode	By screw M3.5
Fixing center	60.3 mm
Embedding depth	>= 35 mm
Rated current	10 A at 250 V AC, fluorescent
[Ue] rated operational voltage	250 V AC
Network frequency	50 Hz
Contacts material	Brass and phosphor bronze
Connections - terminals	Pillar terminal
Terminal identifier	L1 L2
Tightening torque	0.4 N.m
Clamping connection capacity	<= 2.5 mm²
Width	86 mm
Height	86 mm

#### **Environment**

Standards	IEC 60669-1 MS IEC 60669-1 SS 227	
Ambient air temperature for operation	-540 °C	
Relative humidity	095 %	
Environmental characteristic	Indoor use	

### Offer Sustainability

Sustainable offer status	Not Green Premium product
REACh	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

#### Contractual warranty

Period	18 months	

