



Main

Commercial Status	Commercialised
Range of product	Vivace
Device short name	KB31
Product or component type	Dimmer
Device presentation	Complete mechanism

Complementary

Number of gangs	1 gang
Cover frame colour tint	White
Material	Nylon (base) Polycarbonate (surround) Polycarbonate (grid plate)
Projecting depth	8 mm
Device mounting	Flush
Mounting support	Wall mounted
Fixing mode	By screw M3.5
Fixing center	60.3 mm
Embedding depth	>= 35 mm
[Ue] rated operational voltage	220...240 V AC
Network frequency	50 Hz
Power range	400 W (tungsten filament)
Contacts material	Brass and phosphor bronze
Connections - terminals	Pillar terminals
Terminal identifier	Load L
Tightening torque	0.4 N.m
Clamping connection capacity	1.5 mm ²
Width	87 mm
Height	87 mm

Environment

Standards	IEC 60669-2-1
Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Environmental characteristic	Indoor use

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 1101 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold

Contractual warranty

Period	18 months
--------	-----------