



### Main

Commercial Status	Commercialised
Range of product	Vivace
Device short name	KB426
Product or component type	Socket-outlet
Device presentation	Complete mechanism

### Complementary

Outlet poles configuration	2P + E
Number of gangs	1 gang
Cover frame colour tint	White
Material	Nylon (base) Polycarbonate (surround) Polycarbonate (grid plate)
Projecting depth	8 mm
Device mounting	Flush
Mounting support	Wall mounted
Fixing mode	By screw M3.5
Fixing center	60.3 mm
Embedding depth	>= 35 mm
Rated current	13 A at 250 V AC, no inductive load
Network frequency	50 Hz
Contacts material	Brass and phosphor bronze
Connections - terminals	Pillar terminal
Terminal identifier	N L E
Tightening torque	0.4 N.m
Clamping connection capacity	2.5 mm <sup>2</sup> 4 mm <sup>2</sup>
Width	86 mm
Height	86 mm

### Environment

Standards	BS 1363-2 MS 589 SS 145
Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Environmental characteristic	Indoor use

### Offer Sustainability

Sustainable offer status	Not Green Premium product
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available

### Contractual warranty

Period	18 months
--------	-----------