



Main

| | |
|---------------------------|------------------------------|
| Range | ZENcelo |
| Product or component type | Key card switch |
| Rated current | 16 A 220...240 V AC 50/60 Hz |
| Colour tint | Silver bronze |

Complementary

| | |
|------------------------------|--|
| Status LED | LED amber |
| Material | Polycarbonate plastic part |
| Load type | Resistive |
| Device mounting | Surface Flush |
| Connections - terminals | Brass terminal |
| Clamping connection capacity | 2 x 2.5 mm ² solid 3 x 4 mm ² solid 3 x 4 mm ² stranded 2 x 2.5 mm ² stranded |
| Embedding depth | 29.1 mm |
| Width | 87.2 mm |
| Height | 87.2 mm |
| Depth | 41.1 mm |

Environment

| | |
|---------------------------------------|-----------------------------|
| Ambient air temperature for operation | 0...40 °C |
| Relative humidity | 0...95 % |
| Ambient air temperature for storage | 0...60 °C |
| Standards | IEC 60669-2-1 GB 16915.2 |

Offer Sustainability

| | |
|----------------------------------|---|
| Sustainable offer status | Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 1809 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold |
| Product environmental profile | Available |
| Product end of life instructions | Need no specific recycling operations |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|