



Main

Range	ZENcelo
Device application	Electronic application
Product or component type	Key card switch
Rated current	16 A 220...240 V AC 50/60 Hz
Colour tint	Opal sand

Complementary

Status LED	LED amber
Material	Polycarbonate plastic part
Load type	Resistive
Device mounting	Flush Surface
Connections - terminals	Brass terminal
Clamping connection capacity	2 x 2.5 mm ² solid 3 x 4 mm ² solid 3 x 4 mm ² stranded 2 x 2.5 mm ² stranded
Embedding depth	29.1 mm
Width	87.2 mm
Height	87.2 mm
Depth	41.1 mm

Environment

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Ambient air temperature for storage	0...60 °C
Standards	GB 16915.2 IEC 60669-2-1

Disclaimer: Dokumentasi ini tidak ditujukan sebagai pengganti dan tidak untuk digunakan untuk menentukan kesesuaian atau keandalan produk ini untuk aplikasi pengguna

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1809 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations