

E8431EPD4_SZ

1 Gang 350VA, 50Hz Full-Flat Universal Dimmer with LED, Sliver Bronze



Main

Commercial Status	Commercialised
Range of product	ZENcelo
Product or component type	Dimmer
Local signalling	Indicator light LED blue off Indicator light LED amber on
Additional information	With memory push
[Ue] rated operational voltage	220...240 V AC 50 Hz
Material	Steel metal parts Polycarbonate plastic part Brass metal parts
Cover frame colour tint	Silver bronze

Complementary

Wiring device mounting	Flush Surface
Number of cables	3 2.5 mm ² stranded 3 2.5 mm ² solid 2 4 mm ² stranded 2 4 mm ² solid
Rated operational power in VA	350 VA
Number of gangs	1 gang
Load type	Incandescent lamp LV halogen
Embedding depth	6 mm
Width	87 mm
Height	87 mm
Depth	35 mm

Environment

Ambient air temperature for operation	<= 40 °C
Relative humidity	10...95 %
Ambient air temperature for storage	0...60 °C
Standards	IEC 60669-2-1

Contractual warranty

Period	18 months
--------	-----------

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.