



Main

Range	ZENcelo
Product or component type	Switch
Device application	Control
Load type	Inductive
Colour tint	White
Cover frame colour tint	White

Complementary

Number of rocker	2
Device mounting	Flush Surface
Control type	Rocker
Rated current	20 A at 250 V AC 50/60 Hz
Number of gangs	2 gangs
Material	Polycarbonate, for base Polycarbonate, for surround Polycarbonate, for cover Polycarbonate + GF 20 %, for grid plate Polycarbonate, for dolly
Connections - terminals	Brass rod terminals
Embedding depth	23 mm
Width	87 mm
Height	87 mm
Depth	31.5 mm

Environment

Ambient air temperature for operation	-5...35 °C
Relative humidity	0...95 %

Environmental characteristic	No UV resistant
Standards	EN 60669-1 GB 16915.1 IEC 60669-1 MS IEC 60669-1 SS 227-1

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1809 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months 18 months
-----------------	---------------------