

# Lembar data produk

## Karakteristik

# E8432EPD3

## ZENCELO 2 Gang 300VA, 50Hz Full, Flat Universal Dimmer with LED



### Main

Range	ZENcelo
Product or component type	Dimmer
Local signalling	Indicator light LED amber on Indicator light LED blue off
Device application	Communication
Additional information	With memory push
[Ue] rated operational voltage	220...240 V AC 50 Hz
Material	Brass metal parts Polycarbonate plastic part Steel metal parts

### Complementary

Wiring device mounting	Flush Surface
Clamping connection capacity	3 x 2.5 mm <sup>2</sup> for solid cable(s) 3 x 2.5 mm <sup>2</sup> for stranded cable(s) 2 x 4 mm <sup>2</sup> for stranded cable(s) 2 x 4 mm <sup>2</sup> for solid cable(s)
Rated operational power in VA	350 VA
Number of gangs	2 gangs
Load type	Incandescent lamp LV halogen
Embedding depth	6 mm
Width	87 mm
Height	87 mm
Depth	35 mm

### Environment

Ambient air temperature for operation	<= 40 °C
Relative humidity	10...95 %
Ambient air temperature for storage	0...60 °C
Standards	IEC 60669-2-1

## Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 1201 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available